



## **C-17**

## Incredible value and performance: a solid 17" display choice for reliability in home and office environments.

The highly-affordable C-17 offers the vivid image quality, convenient inputs for analogue and digital signals, crisp 60,000:1 dynamic contrast ratio, as well as built-in speakers for multimedia entertainment. With a sleek design and VESA compatible wall mounts that allow for a variety of mounting options, the C-17 is designed perfectly for home use or multi-display office environments where cost is a consideration.

- > Slim and sleek design
- > Economical and durable concern
- > Fast 3ms response time
- > Crisp 60,000:1 dynamic contrast ratio
- > Built-in speakers
- > Auto-adjustment for optimal viewing
- > Kensington® security socket
- > VESA standard wall mount
- > WEEE, RoHS, REACH certified

## **C-17**

| Specifications          |  | C-17   |
|-------------------------|--|--|
| Panel                   | Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments  Viewing Angle (H/V) Display Colour Response Time | TFT LCD 17.0" (432 mm) SXGA 1280 x 1024 0.264 mm 250cd/m2 (Typical) 60,000:1 (DCR) Hard Coating (3H), Anti-glare treatment 160°/160° (Typical) 16.7M 3ms (GTG) |
| Frequency (H/V)         |  | H: 24 kHz - 83 kHz<br>V: 55 Hz - 75 Hz   |
| Input                   | Analogue<br>Digital  | 15-Pin D-Sub<br>24-Pin DVI-D   |
| Audio                   | Audio In<br>Speaker  | 3.5mm Audio Line-in<br>1W x 2  |
| Power                   | AC-DC Adaptor<br>Power<br>Consumption  | Internal AC 100 - 240 V, 50 - 60 Hz < 25 W (On) < 1 W (Stand-by) < 1 W (Off)   |
| Plug & Play             | VESA   | DCC 2B   |
| Operating<br>Conditions | Temperature<br>Humidity  | 0 °C ~ 40 °C<br>10% ~ 85%  |
| Storage<br>Conditions   | Temperature<br>Humidity  | -25 °C ~ 55 °C<br>5% ~ 85%   |
| Mounting                | VESA FPMPMI  | Yes (100 mm)   |
| Tilt                    | Tilt   | -5° ~ +20°   |
| Dimensions              | Product<br>(W x H x D)<br>Packaging<br>(W x H x D)   | 372 x 383 x 190 mm<br>(14.6" x 15.1" x 7.5")<br>448 x 387 x 131 mm<br>(17.6" x 15.2" x 5.2")   |
| Weight                  | Product Weight<br>Packaged Product Weight  | 3.9 kg (8.6 lbs)<br>5.4 kg (11.9 lbs)  |
| Regulation<br>Approval  | Certifications & Compliance  | FCC, CB, CE, GOST-R, WEEE,<br>RoHS, REACH  |
| Accessories             | Supplied   | CD ROM (user manual), 15-Pin<br>D-Sub cable, audio cable, AC<br>power cord   |



Sleek design with anti-glare display panel for superior viewing comfort



VESA standard wall mount allows for secure mounting almost anywhere



Built-in speakers provide easy access to multimedia applications







