

## TLM-0801 Dual Rack Mountable CCTV LED Monitor Specifications:



DESCRIPTION		MODEL	TLM-0801
LCD Panel	Screen Size	8.0 inch diagonal	
	Viewable size	162.0mm (H) x 121.5mm(V)	
	Dot Pitch	0.2025mm x 0.2025mm	
	View angle H/V	-70°, +70°/-70°, +60°	
	Contrast ratio	500:1	
	Brightness	250 cd/m <sup>2</sup>	
	Resolution	800 x 600	
	Response Time	≤50ms	
	Display Color	262K	
	Back Light Type	LED back light	
Control key define		Channel, -, +, Menu, Power	
Power Supply	Input-Voltage	12V <sub>DC</sub>	
	Consumption	7W max.	
Video	Input	Composite video, connector: 2 BNC S-video, connector: 1 mini-din 4 pin Level: 1.0V <sub>p-p</sub> / 75Ω	
	Output	2 BNC connector for CVBS loop-through output,	
	OSD	Contrast, Brightness, Display Adjust, Color Temperature, Language, OSD setting, Aspect Ratio, Audio Control, Input Select, Reset, Exit	
	System Compatibility	Scanning Frequency NTSC : 15750Hz ± 500Hz / 60Hz, PAL : 15625Hz ± 500Hz / 50Hz	
Analog VGA	Input	Analog RGB: 0.707V <sub>p-p</sub> / 75Ω, connector: D-sub 15pins	
	OSD	Contrast, Brightness, Display Adjust, Color Temperature, Language, OSD setting, Audio Control, Input Select, Reset, Exit	
	Plug & Play	EDID	
	Power Management	VESA DPMS	
	Support timing	VESA VGA / SVGA	
Audio	Input/Output	connector: 1 x RCA input/ 1 x RCA output Level: 1.0V <sub>p-p</sub> / 1 KHz	
	Speaker	1W x 1 embedded	
Mechanical	Dimension	202x175.8x29.2mm <sup>3</sup>	
	Weight	2.6lbs (1.17Kg)	
Additional benefit		FCC, CE certified Wall mount pattern 40x40mm <sup>2</sup> Optional Dual Rack Mount Kit TRK-0801 RoHS compliant	

Note: The specifications are subject to change without notice.

