

TLM-1906T TFT LCD Monitor Specification:

| DESCRIPTION | | MODEL | TLM-1906T |
|--------------------|----------------------|---|-----------|
| LCD Panel | Screen Size | 19 inch (diagonal) | |
| | Viewable size | 376.3mm (H) x 301.0mm(V) | |
| | Dot Pitch | 0.294mm x 0.294mm | |
| | View angle H/V | 160(H)/160(V) | |
| | Contrast ratio | 1000:1 | |
| | Brightness | 250 cd/m ² | |
| | Resolution | 1280 x 1024 | |
| | Response Time | 5ms | |
| | Display Color | 16.7M | |
| Control key define | | Channel, Menu, -, +, Power | |
| Power Supply | Input-Voltage | 100~240V _{AC} | |
| | Consumption | 25W max. | |
| Video | Input | Composite video, connector: 1 BNC S-video, connector: 1 mini-din 4 pin Level: 1.0Vp-p / 75Ω | |
| | Output | 1 BNC connector for CVBS loop-through output | |
| | OSD | Contrast, Brightness, Color, Tint, Sharpness, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit | |
| | System Compatibility | Scanning Frequency NTSC : 15750Hz ± 500Hz / 60Hz, PAL : 15625Hz ± 500Hz / 50Hz | |
| Analog VGA | Input | Analog RGB: 0.707Vp-p / 75Ω, connector: 15 pin D-Sub | |
| | OSD | Brightness, Contrast, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit | |
| | Plug & Play | DDC2B | |
| | Power Management | VESA DPMS | |
| | Support timing | VESA VGA / SVGA / XGA / SXGA | |
| Audio | Input/Output | connector: 2 x RCA connector Level: 1.0Vp-p / 1 Khz | |
| | Speaker | 2W x 2 embedded | |
| Mechanical | Dimension | 458x416x215mm (with base), 458x373x77mm (without base) | |
| | Weight | 14.5lbs/6.4Kg (with base) | |
| Additional benefit | | Rack mountable (19" standard rack, EIA-310-D)(Open rack only) VESA mount 100x100mm ² RoHS compliant | |

Note: The specifications are subject to change without notice.