

# CP03 Canopy Light

Power Selectable | Colour Selectable | 120-347V

The successor to our best-selling CP02 Canopy Lights!

Ideal for parking structures, pool areas, gas stations, canopies, and more.  
Suitable for damp/wet locations or wherever a high impact-resistant fixture is required.

6kV Surge Protection  
0-10V dimming



Colour Selectable  
3000K / 4000K / 5000K

Power Selectable  
40W / 60W / 75W

White Powder  
Coat Finish



Faceted Polycarbonate Lens  
for Superior Glare Control,  
Fire and Vandal Resistance

Dropped Lens for  
Improved Beam Angle  
allows for wider  
spacing of luminaires

Universal 120-347V Input

## TECHNICAL DATA



### LIGHT SPECIFICATIONS

Efficacy	123.12 lm/W
CCT	3000K / 4000K / 5000K
CRI	82
Beam Angle	110°
Dimmable	0-10V
L70 Life	>54,000 hrs
Warranty	5-year
Factory Settings	75W   4000K

	3000K	4000K	5000K
75W	8744 lm	9414 lm	9054 lm
60W	7280 lm	8065 lm	7857 lm
40W	5269 lm	5715 lm	5694 lm

### APPROVALS & LISTINGS

cUL	E482965
DLC Premium	S-BEXF8Q

### DIMENSIONS AND WEIGHTS

Fixture Weight	7.41 lbs
Fixture Dimensions	10 x 10 x 4.17 in
Carton Qty	1
Carton Weight	7.62 lbs
Carton Dimensions	12.13 x 6.22 x 12.2 in
Master Carton Qty	2
Master Carton Weight	16.4 lbs
Master Carton Dimensions	13.07 x 12.72 x 12.99 in

### ELECTRICAL

Wattage	40W / 60W / 75W
Voltage	120-347V
Current	1.00A
Surge Protection	6kV
Auxiliary Output	12V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 45°C
Operating Temp (with sensor)	-30 to 45°C

### CONSTRUCTION

Housing	Aluminum Alloy
Lens	Polycarbonate
Finish	Powder Coated
Finish Colour	White
IP Rating	IP65

### ACCESSORIES (Ordered Separately)

Microwave Motion Sensor	MS04-MW-HW-DC
Remote*	HB7B-REMOTE

\*HB7B-REMOTE is **required** for the MS04-MW-HW-DC to function

### DIMENSIONAL DRAWINGS (IN)

