

Accessories

Noise Cancelling Microphone

- Designed to cancel out 90% of back ground noise
- Standard 6 foot (1.82m) coiled cord, retracts to only 1 foot (0.03m)
- Comfortable 3 inch (7.62cm) wide by 4 inch (10.16cm) high microphone body with a large side mounted Push To Talk button.
- Intercom requires the (-7) option, Noise Canceling Microphone Ready Ordering information - ADNCM

Foot Pedal

- For hands free Push To Talk capability
- Heavy duty cast iron construction
- Complies with OSHA requirements for full shielding
- Finished in a bright safety orange paint
- Oil and water tight construction, NEMA rated 2, 4, and 13
- Large 6 inch (15.24cm) wide by 4.5 inch (11.43cm) high pedal opening for ease of operation
- Requires the (-2) option, Foot Pedal Ready

Ordering information - ADFP





Headset and Belt Switch – Available for 120VAC units only

Headset features:

- Under helmet design with adjustable straps
- Noise attenuating technology cancels ambient noise and improves intelligibility
- 220 Ohm noise cancelling microphone

Belt Switch features:

- All necessary jacks for easy connection between headset, belt switch and intercom
- Integrated belt clip
- 15 foot (4.57m) RFI shielded cord
- Large Push To Talk activation button
- Requires (-M34) option, Headset Ready

Ordering information - ADHSB

Auxiliary Strobe Light

- ADLP3S surface mount,
 ADLP3P 1/2" pipe mount
- 175,000 peak candela
- 7000 hour lamp life
- Type 4X, IP66 construction
- Available: Red or Amber lens
- Available: 12-48VDC or 120VAC, 50/60Hz
- Activated by a second intercom equipped with the Call Button (A) and Auxiliary Signal (-3)







| Model | Voltage | Current Draw | Mounting | Color |
|--|--|--|---|---|
| LP3P-012-048A LP3P-012-048R LP3S-012-048A LP3S-012-048R LP3P-120A LP3P-120R LP3S-120A LP3S-120A | 12-48VDC 12-48VDC 12-48VDC 12-48VDC 120VAC 120VAC 120VAC | 0.44 - 0.10 amp 0.44 - 0.10 amp 0.44 - 0.10 amp 0.44 - 0.10 amp 0.10 amp 0.10 amp 0.10 amp | Pipe Pipe Surface Surface Pipe Pipe Surface Surface | Amber Red Amber Red Amber Red Amber |
| LP3P-240A LP3P-240R LP3S-240A LP3S-240R | 240VAC 240VAC 240VAC 240VAC | 0.07 amp 0.07 amp 0.07 amp 0.07 amp | Pipe Pipe Surface Surface | Amber Red Amber Red |

Atkinson Dynamics P: 1.888.751.1500 708.534.4766 Fax: 708.534.4887 www.atkinsondynamics.com