



Panel Mount Intercom

Heavy duty, tamper-resistant Panel-Mount Intercoms, designed for single-channel, two-way communications, integrated volume control, TALK/LISTEN switch, and robust brushed aluminum construction that includes Neoprene TM gasket and stainless steel hardware. Accommodating the full range of Atkinson Dynamics speakers, the flush-mount units are available in 12 or 24VDC and 120 and 240VAC, 50/60Hz models.

- Heavy duty tamper resistant intercom
- Single channel, two way communications
- Integrated volume control and Talk/Listen switch
- Requires a matching Speaker
- Brushed aluminum finish, full gasketed, includes stainless steel hardware
- Available; 12 or 24VDC and 120 240VAC, 50/60Hz



| Model | Voltage | Operating Current | Stand-by Current |
|--------|---------|-------------------|------------------|
| AD-26P | 12VDC | 1.47A | 100mA |
| AD-27P | 120VAC | 240mA | 83 mA |
| AD-56P | 24VDC | 1.65A | 100mA |
| AD-57P | 240VAC | 127mA | 83mA |

Optional Features

- Call Button (A), Sends call tone to other intercoms on the same audio line.
- Master (C), controls Talk/Listen function of a Slave unit.
- Slave (D), allows hands free operation, default Talk mode
- Remote Power (-1), 120VAC unit can supply power to a 12VDC unit remotely.
- Foot Pedal Ready (-2), hands free operation of the Talk/Listen switch, pedal sold separately.
- Auxiliary Signal (-3), remote call button activated contact closure to activate remote strobe for additional attention gathering.
- Zoned System Remote (-6), designed to be a remote unit in a zoned system. Contact factory for zone design assistance.
- Noise Cancelling Microphone Ready (-7), equipped with a jack for hand held microphone sold separately.
- Pre-Amp Equipped (-8), pre-amp to power a remote speaker.
- Headset Ready (-M34), equipped with a jack for use with Head-Set and Belt switch, sold separately.
- Remote Volume Control Equipped (-M44), equipped with volume control for remote speaker.

Note: Some restrictions apply when combining optional features. Consult factory for details.

Product Specifications

| | | |
|-----------------|----------------|---------------|
| Operating temp | -31°F to 150°F | -33°C to 66°C |
| Net weight | 3 lbs | 1.36 Kg |
| Shipping weight | 4 lbs | 1.81 Kg |
| Dimensions | | |
| Height | 4.38 in | 11.26 cm |
| Width | 6.50 in | 16.51 cm |
| Depth | 3.36 in | 8.53 cm |

