

# Mini Flood Light

55W / 70W / 80W | 3CCT | 120-347V

Meet the successor to our best-selling FLM Mini Flood Lights!

Ideal for landscaping, patio, and security lighting, signs and building facades

Excellent replacement for quartz halogen fixtures

**Die-Cast  
Aluminum Housing**  
with cooling fins for  
superior heat dissipation



**Power Selectable**  
55W / 70W / 80W

**Built-in Photocell**

**64 LED Chips**  
for even illumination

**8" Power Cord**

**High-Impact  
Polycarbonate  
Lens/Optics**

**Complete With  
Yoke Mount**  
interchangeable mounting  
options sold separately



**Colour Selectable**  
3000K / 4000K / 5000K

**Rugged Polyester  
Powder Coat Finish**  
(Bronze)



## TECHNICAL DATA

### LIGHT SPECIFICATIONS

Lumens	10,326 lm
Efficacy	128.3 lm/W
CCT	3000K/4000K/5000K
Distribution	NEMA 7x7
CRI	82
Dimmable	0-10V
L70 Life	> 54,000 hrs
Warranty	10-year
Factory Settings	80W   4000K

LUMEN OUTPUT			
	3000K	4000K	5000K
<b>55W</b>	8,411 lm	9,002 lm	8,443 lm
<b>70W</b>	9,569 lm	10,462 lm	10,031 lm
<b>80W</b>	10,326 lm	11,270 lm	11,057 lm

### APPROVALS AND LISTINGS

cUL	E482965
DLC	S-YMB16N

### ACCESSORIES (SOLD SEPARATELY)

Knuckle Mount	FLM02-KN
Slip Fitter	FL-SF01-BZ
Pole Mount	FL-PM01-BZ
Multi Mount	FL-MM01-BZ
Ratchet Yoke Mount	FLM02-BKT-LG

**NOTE:** FLM02-BKT-LG is **REQUIRED** in order to use the Pole Mount, Slip Fitter, and Multi Mount.

### ELECTRICAL

Wattage	55W / 70W / 80W
Voltage	120-347V
Current	0.7A
Surge Protection	2.5kV
Auxiliary Output	N/A
Power Factor	0.9
THD	15%
Operating Temp	-30°C to 45°C

### CONSTRUCTION

Power Cord	8"
Housing	Die-Cast Aluminum
Finish	Polyester Powder Coat
Finish Colour	Bronze
IP Rating	IP65

### DIMENSIONS

Fixture Weight	3.3 lbs
Fixture Dimensions	9.37" x 1.97" x 8.07"
Carton Qty	1
Carton Weight	3.96 lbs
Carton Dimensions	10.8" x 3" x 12.2"
Master Carton Qty	6
Master Carton Weight	25.3 lbs
Master Carton Dimensions	18.5" x 12.8" x 11.6"

### ILLUMINANCE AT A DISTANCE

