

1'x 4' Premium Panel

20W, 30W, 40W Selectable | Colour Selectable | 120-347V

High performance, light-weight luminaires suitable for lay-in, surface or suspension mounting. Ideal for use in schools, health care applications, offices, retail spaces, and more

0-10V Dimming Lead on Both Sides of Driver Junction Box

Use Switches to Select Colour Temperature and Wattage



Non-yellowing Prismatic Lens



120-347V, 0-10V Dimmable Driver

Seismic Clips Included



Colour Selectable
(3000K / 3500K / 4000K)

Power Selectable
(20W / 30W / 40W)

Less than 1.8" Deep
ideal for tight plenum areas

Waffle Stamping
increases heat dissipation and driver life



Junction Box (PLS-JB)
sold separately

Accessories (Sold Separately)



Suspension Kit
PLS-SUSKIT



Surface Mount Kit
PLS14-SK



Junction Box
PLS-JB



Recessed Frame Kit
PLS14-RFK

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	5,000 lms @ 3000K
Efficacy	125 lm/W
CCT	Selectable (30K/35K/40K)
CRI	80
Dimmable	0-10V
Beam Angle	120°
L70 Life	50,000 hrs
Warranty	7-year
Factory Settings	40W 4000K

LUMEN OUTPUT			
	3000K	3500K	4000K
20W	2844 lm	3071 lm	2927 lm
30W	4063 lm	4400 lm	4213 lm
40W	4838 lm	5203 lm	4938 lm

APPROVALS AND LISTINGS

ETL	5000444
DLC Premium	S-FUY7QN, S-1NQNWL

ILLUMINANCE AT A DISTANCE

	Illuminance at a Distance		
	Center Beam fc	Beam Width	
17.0ft	7.92 fc	36.2 ft	34.2 ft
34.0ft	1.98 fc	72.5 ft	68.4 ft
51.0ft	0.88 fc	108.7 ft	102.6 ft
68.0ft	0.49 fc	145.0 ft	136.8 ft
85.0ft	0.32 fc	181.2 ft	171.0 ft
102.0ft	0.22 fc	217.5 ft	205.2 ft

■ Vert. Spread: 93.7°
■ Horiz. Spread: 90.3°

ELECTRICAL

Wattage	Selectable (20W/30W/40W)
Voltage	120-347V
Power Factor	0.90
THD	8%
Operating Temp	-20 to 40°C

CONSTRUCTION

Housing	Metal
Lens Type	Prismatic
Finish	White
IP Rating	IP20
Product Dimensions	47.72 x 11.85 x 1.67 in
Carton Qty	4

ACCESSORIES (SOLD SEPARATELY)

PLS14-SK	Surface Mount Kit
PLS14-RFK	Recessed Frame Kit
PLS-SUSKIT	Suspension Kit
PLS-JB	Junction Box

DIMENSIONAL DRAWINGS (IN)

