

Pole Top Area Light

35W | Colour Selectable | 120-347V

Elegant look and design
Ideal for parking lots, pathways, parks, retail settings, and more

Colour Selectable
3000K / 4000K / 5000K

0-10V Dimmable

Polyester
Powder-Coat Finish
Bronze

Instant Start

Complete with
Photocell Receptacle
and Shorting Cap
Photocells sold separately

High-Efficiency
Optics
with type 5 distribution



Easily Adjustable

Fits Up To 2 3/4" OD pole



TECHNICAL DATA



LIGHT SPECIFICATIONS

Efficacy	122.8 lm/W @ 3000K
CCT	3000K / 4000K / 5000K
CRI	83
Distribution	Type V
Beam Angle	90°
Dimmable	0-10V
L70 Life	>50,000 hours
Warranty	10-year
Factory Settings	35W 4000K

LUMEN OUTPUT TABLE			
	3000K	4000K	5000K
35W	4340 lm	4655 lm	4480 lm

DIMENSIONS AND WEIGHTS

Fixture Weight	10.12 lbs
Fixture Dimensions	13.4 x 13.4 x 7.3 in
Carton Qty	1
Carton Weight	12.54 lbs
Carton Dimensions	28.7 x 20.3 x 7.1 in

APPROVALS AND LISTINGS

cUL	E482965
DLC	S-2Y39FM

ELECTRICAL

Wattage	35W
Voltage	120-347V
Current	0.389A
Surge Protection	4kV
Auxiliary Output	N/A
Power Factor	0.93
THD	16.7%
Operating temp	-40 to 50°C

CONSTRUCTION

Power Cord	23"
Housing	Aluminum
Finish	Powder coated
Finish Colour	Bronze
Lens	Polycarbonate
IP Rating	IP65

ACCESSORIES (SOLD SEPARATELY)

120-347V Photocell	JL-207E
120-277V Photocell	JL-205LV

DIMENSIONAL DRAWING (IN)

